

May 14, 2013

WTP NOI Division of Water Pollution Control 6th Floor L & C Annex, 401 Church Street Nashville, Tennessee 37243

Cookeville Water Treatment Plant Re:

NOI, Presently Covered by NPDES Permit # TN0005231

To whom it may concern:

Please find enclosed the original and one copy of the NOI for coverage under the General Permit Water Treatment Plant Discharge for the discharge from the Cookeville Water Treatment Plant Lagoon Discharge.

If you have any questions regarding this matter, feel free to call me at (931) 520-5258.

Sincerely,

Barry K. Turner, P.E.

Environmental Engineer

Barry K. June

Enclosures

RECEIVED MAY 1 5 2013

TN Division Of Water Pollution Control



Facility Name: CITY OF COOKEVILLE WATER TREATMENT PLANT

DEPARTMENT OF ENVIRONMENT AND CONSERVATION DIVISION OF WATER POLLUTION CONTROL

NOTICE OF INTENT (NOI) WATER TREATMENT PLANT DISCHARGE PERMIT

County: PUTNAM

	cation: 9722 WA			38544		_	gitude:	85°40'	41 1
	*********	Attach a copy of U.S.G.S. topog	ranhical man, a cit	v man or a cou	nty man identify	ving the loc	ation of th		■ This NOI
		ble corporate officer for a corpor							
execu	itive officer or ranking el	ected official for a public agency.	If this NOI is sub	mitted because of	f new operator or	to update fa	acility info		
of fac	cility, new official contac	t person name, new E-mail address	s, etc.), provide the	existing permit tr	acking number: _	TN000523	<u>1</u>		
Owne	er or Operator: (the perso	n or legal entity which controls fac	cility's operation; th	is may or may no	ot be the same as t	the site name	e or the off	icial contac	et name)
eri Ngjarja		COOKEVILLE DEPAR			13-14-138-W60-V4-13988-V5-V5-0				12 2 2
		Name: (individual responsible for		e or Position:	DEFT. COULT	1011			3 (24) (1 (1) <u>5</u> (24) (1 (1) (1) (1 (1) (1) (1 (1) (1) (1 (1) (1)
	RONNIE				OR DEPT O	F WATE	R OTTAT	TTY C	ONTROL
	Mailing Address:		Cit		<u> </u>	Stat		Zip:	ONTINOL
1)	1860 S	JEFFERSON AVE		COOKEV	ILLE	T	N	3850	6
9	Phone:		E-n	nail:					
	(931) 520-52	227		RJK@CO	OKEVILLE-	TN.ORG			
	Local Contact Person N	Name: (if appropriate, write "same	as #1") Titl	e or Position;					
		PHILLIPS	45 "1"		PERINTEND	ENT			
_		may or may not be the same as stre	eet address) Fac	ility City:	DICTIVE DIVE	Stat	te:	Zip:	
2		ATER PLANT ROAD		BAXTER		TN		3854	4
	Phone:		E-n	nail:	• • •		I	· · · · · · · · · · · · · · · · · · ·	
	(931) 858-26			WATERPI	LANT@COOK	EVILLE-	-TN.OF	RG	
			x (to the right) or cir	cle the number (a	above) to indicate	where to se	nd corresp	ondence:	1
PRA	CESS DESCRIPTIO	N (Reply on a separate page	if necessary)					l	
		ing the discharge (and the mileage	• • • • • • • • • • • • • • • • • • • •						
IName	e of surface waters receiv	ing the discharge land the mileage	e noint it available).						
		- · · · · ·							
CEI	NTER HILL LAK	E-DITCH @0.1 TO A	LUM LICK B						
CEN A des	NTER HILL LAK cription of the plant, i.e.	- · · · · ·	LUM LICK B						
CEN A des oxidiz	NTER HILL LAK scription of the plant, i.e. ging enhancers, etc.	E-DITCH @0.1 TO A iron removal, manganese and/or to	LUM LICK B urbidity removal, an	d a list of any ad	ditives used in the				
CEN A des oxidiz	NTER HILL LAK scription of the plant, i.e. ging enhancers, etc.	E-DITCH @0.1 TO A	LUM LICK B urbidity removal, an	d a list of any ad	ditives used in the				
CEN A des oxidiz A V	NTER HILL LAK cription of the plant, i.e. zing enhancers etc. NYENTIONAL WATER PLANT U	E-DITCH @0.1 TO A iron removal, manganese and/or to SING FERRIC CHLOR	LUM LICK Burbidity removal, an	d a list of any ad	ditives used in the	e water treat	ment proce	ess, such as	coagulant,
CENA des oxidiz A V	NTER HILL LAK cription of the plant, i.e. zing enhances, etc. NYENTIONAL WATER PLANT U cn capacity of treatment p	E-DITCH @0.1 TO A iron removal, manganese and/or to SING FERRIC CHLOR plant in million of gallons per day (LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 1	d a list of any ad COAGULAI Jumber and volu	ditives used in the	e water treat	ment proce	ess, such as	coagulant,
CEN A des oxidiz A V Desig	NTER HILL LAK cription of the plant, i.e. zing enhances, etc. NYENTIONAL WATER PLANT U cn capacity of treatment p	E-DITCH @0.1 TO A iron removal, manganese and/or to SING FERRIC CHLOR	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 1	d a list of any ad COAGULAI Jumber and volu	ditives used in the	e water treat	ment proce	ess, such as	coagulant,
CEN A des oxidiz A V Desig Avera	NTER HILL LAK cription of the plant, i.e. zing enhances, etc. NYENTIONAL WATER PLANT U cn capacity of treatment p	E-DITCH @0.1 TO A iron removal, manganese and/or to SING FERRIC CHLOR plant in million of gallons per day (or production in MGD over 12 mon	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 1	COAGULAI Tumber and volution of the NOI:	ditives used in the NT. me of sedimentati 9.4 MGD	e water treati	ment proce	ess, such as	coagulant, GALLONS
CENA dessoxidized A V Desig Avera	NTER HILL LAK coription of the plant, i.e. zing enhancers, etc. NATER PLANT U cn capacity of treatment p age flow of finished wate backwashing. Number 0,000 for each file	E-DITCH @0.1 TO A iron removal, manganese and/or to ISING FERRIC CHLOR plant in million of gallons per day (or production in MGD over 12 monof filter backwashed: 8 ter. Frequency sedimentation basing the production in MGD over 12 monof filter backwashed: 8 ter. Frequency sedimentation basing the production is the production of the production of the production is the production of the production of the production is the production of the production of the production is the production of the pro	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 1 this prior to submiss Frequency for each is washed out:	COAGULAI Winnber and volution of the NOI: a filter: 1.8 2 times pe	MT. me of sedimentati 9.4 MGD times per week r year. Amount of	e water treation basins: 4	ment proce 4 - 31 f water use to wash or	L2,000 d to backwut the large	GALLONS
CENA des oxidiz A V Desig Avera	NTER HILL LAK coription of the plant, i.e. zing enhancers, etc. NATER PLANT U cn capacity of treatment p age flow of finished wate backwashing. Number 0,000 for each file	E-DITCH @0.1 TO A iron removal, manganese and/or to ISING FERRIC CHLOR plant in million of gallons per day (or production in MGD over 12 monof filter backwashed: 8	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 1 this prior to submiss Frequency for each is washed out:	COAGULAI Winnber and volution of the NOI: a filter: 1.8 2 times pe	MT. me of sedimentati 9.4 MGD times per week r year. Amount of	e water treation basins: 4	ment proce 4 - 31 f water use to wash or	L2,000 d to backwut the large	GALLONS
A des oxidiz A V Desig Avera	NTER HILL LAK coription of the plant, i.e. zing enhancers, etc. NATER PLANT U cn capacity of treatment p age flow of finished wate backwashing. Number 0,000 for each file	E-DITCH @0.1 TO A iron removal, manganese and/or to ISING FERRIC CHLOR plant in million of gallons per day (or production in MGD over 12 monof filter backwashed: 8 ter. Frequency sedimentation basing the production in MGD over 12 monof filter backwashed: 8 ter. Frequency sedimentation basing the production is the production of the production of the production is the production of the production of the production is the production of the production of the production is the production of the pro	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 1 this prior to submiss Frequency for each is washed out:	COAGULAI Winnber and volution of the NOI: a filter: 1.8 2 times pe	MT. me of sedimentati 9.4 MGD times per week r year. Amount of	e water treation basins: 4	ment proce 4 - 31 f water use to wash or	L2,000 d to backwut the large	GALLONS
A des oxidiz A V Desig Avera Filter 280 sedim	NTER HILL LAK cription of the plant, i.e. zing enhancers, etc. NYENTIONAL WATER PLANT U cn capacity of treatment p age flow of finished wate backwashing. Number 0,000 for each fil- mentation basin 20,000ga r is released from the back	IE-DITCH @0.1 TO A iron removal, manganese and/or to a siron removal remov	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 n this prior to submiss Frequency for each is washed out: for backwash and so er week for	COAGULAN COAGUL	me of sedimentati 9.4 MGD _times per week r year. Amount of in washwaters and	ion basins: 4 c. Amount of f water used d the design	f water use to wash or capacity o	L2,000 d to backwut the large	GALLON S
A des oxidiz A V Desig Avera 280 Sedim	NTER HILL LAK corription of the plant, i.e. zing enhancers, etc. NATER PLANT U cn capacity of treatment p age flow of finished wate backwashing. Number 0,000 for each fil- nentation basin20,000ga r is released from the bac ty, give averages from las	IE-DITCH @0.1 TO A iron removal, manganese and/or to ISING FERRIC CHLOR plant in million of gallons per day (or production in MGD over 12 monor of filter backwashed: 8 ter. Frequency sedimentation basin llons. Type of treatment provided	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 n this prior to submiss Frequency for each is washed out: for backwash and so er week for	COAGULAN COAGUL	me of sedimentati 9.4 MGD _times per week r year. Amount of in washwaters and	ion basins: 4 c. Amount of f water used d the design	f water use to wash or capacity o	ess, such as L2,000 ad to backwut the large f the treatm	GALLON S
A des oxidiz A V Desig Avera 280 Sedim	NTER HILL LAK cription of the plant, i.e. zing enhancers, etc. NYENTIONAL WATER PLANT U cn capacity of treatment p age flow of finished wate backwashing. Number 0,000 for each fil- mentation basin 20,000ga r is released from the back	IE-DITCH @0.1 TO A iron removal, manganese and/or to a siron removal remov	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 n this prior to submiss Frequency for each is washed out: for backwash and so er week for	COAGULAN COAGUL	me of sedimentati 9.4 MGD _times per week r year. Amount of in washwaters and	ion basins: 4 c. Amount of f water used d the design	f water use to wash or capacity o	ess, such as L2,000 ad to backwut the large f the treatm	GALLON S
A des oxidization A V Desig Avera P Filter 280 sedim Water facilit CON	NTER HILL LAK cription of the plant, i.e. zing enhancers, etc. NATER PLANT U cription of treatment p age flow of finished wate backwashing. Number 0,000 for each fil- lentation basin20,000ga r is released from the bac ty, give averages from las	E-DITCH @0.1 TO A iron removal, manganese and/or to ISING FERRIC CHLOR plant in million of gallons per day (or production in MGD over 12 monof filter backwashed: 8 ter. Frequency sedimentation basin llons. Type of treatment provided kwash settling basin times per 12 months of operation. For new	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 n this prior to submiss Frequency for each is washed out: for backwash and so er week for	COAGULAN COAGUL	me of sedimentati 9.4 MGD _times per week r year. Amount of in washwaters and	ion basins: 4 c. Amount of f water used d the design	f water use to wash or capacity o	ess, such as L2,000 ad to backwut the large f the treatm	GALLON S
A des oxidizados A V Desig Avera 280 Sedim Water facilit CON	NTER HILL LAK corription of the plant, i.e. zing enhancers, etc. NATER PLANT U concapacity of treatment page flow of finished wate backwashing. Number 0,000 for each file centation basin 20,000 r is released from the bac y, give averages from las NTINUOUS TIFICATION AND	IE-DITCH @0.1 TO A iron removal, manganese and/or to ISING FERRIC CHLOR plant in million of gallons per day (or production in MGD over 12 monor of filter backwashed: 8 ter. Frequency sedimentation basin llons. Type of treatment provided kwash settling basin times post 12 months of operation. For new SIGNATURE	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 r ths prior to submiss Frequency for each in is washed out: for backwash and so er week for v facilities, indicate	COAGULAI COAGULAI Rumber and volution of the NOI: a filter: 1.8 mathrmal times periodimentation bas hours per release not available.	me of sedimentati 9.4 MGD times per week r year. Amount of in washwaters and se and a volume of Describe more ful	ion basins: 4 c. Amount of f water used d the design f gally, if necess	f water use to wash or capacity o	ess, such as L2,000 ed to backwut the large f the treatmelease. For	GALLON States and the states are system.
A des oxidizados A V Desig Avera 280 A V Desig Avera 280 CER I certificación de CER	NTER HILL LAK coription of the plant, i.e. zing enhancers, etc. NATER PLANT U corn capacity of treatment p age flow of finished wate backwashing. Number 0,000 for each fil- nentation basin 20,000ga r is released from the bac ty, give averages from las NTINUOUS TIFICATION AND a ify under penalty of law	IE-DITCH @0.1 TO A iron removal, manganese and/or to ISING FERRIC CHLOR of production in MGD over 12 monor of filter backwashed: 8 ter. Frequency sedimentation basin llons. Type of treatment provided wash settling basin times per table to the production. For new the set 12 months of operation. For new that this document and all attach	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 1 this prior to submiss Frequency for each in is washed out: for backwash and so er week for v facilities, indicate of	d a list of any ad COAGULAI dumber and volution of the NOI: a filter: 1.8 1 times perdimentation bas hours per release not available.	me of sedimentati 9.4 MGD _times per week r year. Amount of in washwaters and se and a volume of Describe more full ction or supervisi	ion basins: 4 c. Amount of f water used d the design f ga lly, if necess	f water use to wash or capacity o llons per retary.	ess, such as 12,000 ed to backwut the large f the treatmelelease. For	GALLONS ash: st lent system. existing designed to
CENA des oxidizados A V Desig Avera Avera 280 Sedim Water facilit CON CER I certifassure	NTER HILL LAK coription of the plant, i.e. zing enhancers, etc. NATER PLANT U en capacity of treatment p age flow of finished wate backwashing. Number 0,000 for each fil- nentation basin 20,000 r is released from the bac ety, give averages from las NTINUOUS TIFICATION AND ify under penalty of law et that qualified personnel	E-DITCH @0.1 TO A iron removal, manganese and/or to ISING FERRIC CHLOR of plant in million of gallons per day (or production in MGD over 12 monor of filter backwashed: 8 ter. Frequency sedimentation basin llons. Type of treatment provided wash settling basin times per treatment provided it is to properly gather and all attach properly gather and evaluate the	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15	COAGULAI COAGUL	me of sedimentati 9.4 MGD _times per week r year. Amount of in washwaters and se and a volume of Describe more full ction or supervisi y inquiry of the p	ion basins: 4 c. Amount of water used d the design f gally, if necession in accorderson or per	f water use to wash or capacity o llons per reary.	ed to backwut the large f the treatmelease. For	GALLONS Tash: st teent system. existing designed to e system, or
CEN A des A des A V Desig AAvera Filter 280 sedim Water facilit CON CER I certii	NTER HILL LAK accipition of the plant, i.e. zing enhancers, etc. WATER PLANT U an capacity of treatment p age flow of finished wate backwashing. Number 0,000 for each fil- lentation basin 20,000 ar is released from the bac by, give averages from las NTINUOUS TIFICATION AND ify under penalty of law that qualified personnel persons directly responsi	IE-DITCH @0.1 TO A iron removal, manganese and/or to ISING FERRIC CHLOR olant in million of gallons per day (or production in MGD over 12 monor of filter backwashed: 8 ter. Frequency sedimentation basin llons. Type of treatment provided kwash settling basin times per tallow the months of operation. For new that this document and all attach properly gather and evaluate the lible for gathering the information.	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 r this prior to submiss Frequency for each is washed out: for backwash and so er week for v facilities, indicate of unents were prepare information submit the information sub-	d a list of any ad COAGULAI Jumber and volution of the NOI: In filter: 1.8 Limes per dimentation base in a variable. d under my directed. Based on momitted is, to the	me of sedimentati 9.4 MGD _ times per week r year. Amount of in washwaters and se and a volume o Describe more ful ction or supervisi y inquiry of the p	ion basins: 4 c. Amount of water used d the design f gally, if necession in accorders on or peredge and be	f water use to wash or capacity of the capacit	ed to backwut the large of the treatmelease. For	GALLONS rash: st hent system. existing designed to be system, or d complete.
CEN A des A des A V Desig AAvera Filter 280 sedim Water facilit CON CER I certii	NTER HILL LAK accipition of the plant, i.e. zing enhancers, etc. WATER PLANT U an capacity of treatment p age flow of finished wate backwashing. Number 0,000 for each fil- lentation basin 20,000 ar is released from the bac by, give averages from las NTINUOUS TIFICATION AND ify under penalty of law that qualified personnel persons directly responsi	IE-DITCH @0.1 TO A iron removal, manganese and/or to ISING FERRIC CHLOR plant in million of gallons per day (or production in MGD over 12 monor of filter backwashed: 8 ter. Frequency sedimentation basis llons. Type of treatment provided kwash settling basin times post 12 months of operation. For new that this document and all attach properly gather and evaluate the lible for gathering the information, ficant penalties for submitting fals	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 r this prior to submiss Frequency for each is washed out: for backwash and so er week for v facilities, indicate of unents were prepare information submit the information sub-	d a list of any ad COAGULAI Jumber and volution of the NOI: In filter: 1.8 Limes per dimentation base in a variable. d under my directed. Based on momitted is, to the	me of sedimentati 9.4 MGD _ times per week r year. Amount of in washwaters and se and a volume o Describe more ful ction or supervisi y inquiry of the p	ion basins: 4 c. Amount of water used d the design f gally, if necession in accorders on or peredge and be	f water use to wash or capacity of the capacit	ed to backwut the large of the treatmelease. For	GALLONS rash: st hent system. existing designed to be system, or d complete.
CEN A des soxidizados A des soxidizados A Vana de Vana	NTER HILL LAK accipition of the plant, i.e. zing enhancers, etc. WATER PLANT U an capacity of treatment p age flow of finished wate backwashing. Number 0,000 for each fil- lentation basin 20,000 ar is released from the bac by, give averages from las NTINUOUS TIFICATION AND ify under penalty of law that qualified personnel persons directly responsi	IE-DITCH @0.1 TO A iron removal, manganese and/or to ISING FERRIC CHLOR olant in million of gallons per day (or production in MGD over 12 monor of filter backwashed: 8 ter. Frequency sedimentation basin llons. Type of treatment provided kwash settling basin times per tallow the months of operation. For new that this document and all attach properly gather and evaluate the lible for gathering the information.	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 r this prior to submiss Frequency for each is washed out: for backwash and so er week for v facilities, indicate of unents were prepare information submit the information sub-	d a list of any ad COAGULAI Jumber and volution of the NOI: In filter: 1.8 Limes per dimentation base in a variable. d under my directed. Based on momitted is, to the	me of sedimentati 9.4 MGD _ times per week r year. Amount of in washwaters and se and a volume o Describe more ful ction or supervisi y inquiry of the p	ion basins: 4 c. Amount of water used d the design f gally, if necession in accorders on or peredge and be	f water use to wash or capacity of the capacit	ed to backwut the large of the treatmelease. For	GALLONS rash: st hent system. existing designed to be system, or d complete.
CEN A dess oxidiz A V Desig Avera Filter 280 sedim Water facilit CON CER I certifi those I am a RON	NTER HILL LAK coription of the plant, i.e. zing enhancers, etc. NATER PLANT U con capacity of treatment p age flow of finished wate backwashing. Number 0,000 for each file centation basin 20,000 r is released from the backy, give averages from las NTINUOUS TIFICATION AND ify under penalty of law that qualified personnel persons directly responsionaware that there are significations.	IE-DITCH @0.1 TO A iron removal, manganese and/or to ISING FERRIC CHLOR plant in million of gallons per day (or production in MGD over 12 monor of filter backwashed: 8 ter. Frequency sedimentation basis llons. Type of treatment provided kwash settling basin times post 12 months of operation. For new that this document and all attach properly gather and evaluate the lible for gathering the information, ficant penalties for submitting fals	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 r this prior to submiss Frequency for each is washed out: for backwash and so er week for v facilities, indicate of unents were prepare information submit the information sub-	d a list of any ad COAGULAI Jumber and volution of the NOI: In filter: 1.8 Limes per dimentation base in a variable. d under my directed. Based on momitted is, to the	me of sedimentati 9.4 MGD _times per week r year. Amount of in washwaters and se and a volume o Describe more ful ction or supervisi y inquiry of the p best of my knowle ity of fine and imp	ion basins: 4 c. Amount of water used d the design f gally, if necession in accorders on or peredge and be	f water use to wash or capacity of the capacit	ed to backwut the large of the treatmelelease. For manage the accurate, and giviolation	GALLONS rash: st hent system. existing designed to be system, or d complete.
CEN A dess oxidizate A V Desig Avera Filter 280 Sedim Water facilit CON CER I certifassure those I am a RON Printe	NTER HILL LAK coription of the plant, i.e. zing enhancers, etc. NATER PLANT U con capacity of treatment p age flow of finished wate backwashing. Number 0,000 for each fil- mentation basin 20,000ga r is released from the bac ty, give averages from las NTINUOUS TIFICATION AND if ify under penalty of law e that qualified personnel persons directly responsi- aware that there are significant. NNIE KELLY ed Name	iron removal, manganese and/or to a siron removal filling for a siron filler backwashed: 8 ter. Frequency sedimentation basin llons. Type of treatment provided a siron for treatment provided a siron for new a siron for new a siron for a siron for new a siron for gathering the information, ficant penalties for submitting fals a DIRECTOR	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 r this prior to submiss Frequency for each is washed out: for backwash and so er week for v facilities, indicate of unents were prepare information submit the information sub-	d a list of any ad COAGULAI Jumber and volution of the NOI: In filter: 1.8 Limes per dimentation base hours per release frot available. d under my directed. Based on momitted is, to the ding the possibil	me of sedimentati 9.4 MGD _times per week r year. Amount of in washwaters and se and a volume o Describe more ful ction or supervisi y inquiry of the p best of my knowle ity of fine and imp	ion basins: 4 c. Amount of water used d the design f gally, if necession in accorders on or peredge and be	f water use to wash or capacity o llons per reary.	ed to backwut the large of the treatmelelease. For manage the accurate, and giviolation	GALLONS rash: st hent system. existing designed to be system, or d complete.
A dessociation of the control of the	NTER HILL LAK accipition of the plant, i.e. zing enhancers, etc. NATER PLANT U an capacity of treatment p age flow of finished wate backwashing. Number 0,000 for each file aentation basin 20,000 ar is released from the backy, give averages from las NTINUOUS TIFICATION AND ify under penalty of law be that qualified personnel persons directly responsive aware that there are significant.	IE-DITCH @0.1 TO A iron removal, manganese and/or to ISING FERRIC CHLOR of production in MGD over 12 monor of filter backwashed: 8 ter. Frequency sedimentation basin llons. Type of treatment provided kwash settling basin times post 12 months of operation. For new to 12 months of operation. For new to 12 months of operation times post 12 months of operation. For new to 15 months of operation to 16 months of operation times post 12 months of operation. For new to 15 months of operation of the formation, ficant penalties for submitting fals of IRECTOR Official Title	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 r this prior to submiss Frequency for each is washed out: for backwash and so er week for v facilities, indicate of unents were prepare information submit the information sub-	d a list of any ad COAGULAI Rumber and volution of the NOI: a filter: 1.8 mathematical times periodimentation based in a variable. d under my directed based on momitted is, to the ding the possibil	me of sedimentati 9.4 MGD _times per week r year. Amount of in washwaters and se and a volume o Describe more ful ction or supervisi y inquiry of the p best of my knowle ity of fine and imp	ion basins: 4 c. Amount of water used d the design f gally, if necession in accorders on or peredge and be	f water use to wash or capacity o llons per reary.	ed to backwut the large of the treatmelelease. For manage the accurate, and giviolation	GALLONS rash: st hent system. existing designed to be system, or d complete.
CEN A dess oxidiz A V Desig Avera Filter 280 sedim Water facilit CON CER I certi assure those I am a RON Printe STA	NTER HILL LAK coription of the plant, i.e. zing enhancers, etc. NATER PLANT U con capacity of treatment p age flow of finished wate backwashing. Number 0,000 for each fil- nentation basin 20,000 ga r is released from the bac ty, give averages from las NTINUOUS TIFICATION AND if ify under penalty of law e that qualified personnel persons directly responsi aware that there are significant. NNIE KELLY ed Name TE USE ONLY	IE-DITCH @0.1 TO A iron removal, manganese and/or to ISING FERRIC CHLOR of production in MGD over 12 monor of filter backwashed: 8 ter. Frequency sedimentation basin llons. Type of treatment provided kwash settling basin times post 12 months of operation. For new to 12 months of operation. For new to 12 months of operation times post 12 months of operation. For new to 15 months of operation to 16 months of operation times post 12 months of operation. For new to 15 months of operation of the formation, ficant penalties for submitting fals of IRECTOR Official Title	LUM LICK B urbidity removal, an IDE AS THE (MGD): 15 n this prior to submiss Frequency for each is washed out: for backwash and so er week for v facilities, indicate unents were prepare information submit the information, inclu-	d a list of any ad COAGULAI Jumber and volution of the NOI: In filter: 1.8 Times per dimentation base from available. d under my directed. Based on me mitted is, to the ding the possibility of the ding the possibility of the ding the possibility.	me of sedimentati 9.4 MGD _ times per week r year. Amount of in washwaters and se and a volume of Describe more ful ction or supervisity inquiry of the p best of my knowle ity of fine and imp	ion basins: 4 c. Amount of water used d the design f gally, if necession in accorders on or peredge and be	f water use to wash or capacity o llons per resary.	ed to backwut the large of the treatmelease. For manage the accurate, and go violation of the large of the treatmeles.	GALLONS rash: st hent system. existing designed to be system, or d complete.

RECEIVED

WTP NOI **Division of Water Pollution Control** 6th Floor L&C Annex, 401 Church Street Nashville, TN 37243-1534

CN-1225

MAY 1 5 2013

RDAs 2399 and 2400